

# PA 塑料电缆软管

## Poleon




材质 PA 尼龙塑料

RoHS

环境温度 - 40 °C – 120 °C (-40°F – 248°F)

颜色 灰 (RAL 7031), 黑 (RAL 9005)

注:  
- 原材料符合 UL 94




尺寸	d mm	D mm	R mm	订货号 灰	订货号 黑
6	6,5	10	15	1.510.0600.14	1.510.0601.14
10	10	13	25	1.510.0900.14	1.510.0901.14
12	12	15,8	35	1.510.1100.14	1.510.1101.14
14	14,2	18,4	35	1.510.1300.14	1.510.1301.14
17	16,5	21,2	40	1.510.1600.14	1.510.1601.14
23	23	28,4	45	1.510.2100.14	1.510.2101.14
29	29	34,5	55	1.510.2900.14	1.510.2901.14
37	36	42,5	65	1.510.3600.14	1.510.3601.14
50	48	54,5	80	1.510.4800.14	1.510.4801.14

## Poleon Slit

**RoHS**

材质	PA 尼龙塑料
环境温度	- 40 °C – 120 °C (-40°F – 248°F)
颜色	灰 (RAL 7031), 黑 (RAL 9005)

注：  
- 原材料符合 UL94



尺寸	d mm	D mm	R mm	订货号 灰	订货号 黑
6	6,5	10	15	1.527.0600.00	1.527.0601.00
10	10	13	25	1.527.0900.00	1.527.0901.00
12	12	15,8	35	1.527.1100.00	1.527.1101.00
14	14,2	18,4	35	1.527.1300.00	1.527.1301.00
17	16,5	21,2	40	1.527.1600.00	1.527.1601.00
23	23	28,4	45	1.527.2100.00	1.527.2101.00
29	29	34,5	55	1.527.2900.00	1.527.2901.00
37	36	42,5	65	1.527.3600.00	1.527.3601.00
50	48	54,5	80	1.527.4800.00	1.527.4801.00