


# 危险场所用电缆接头

**EXIOS<sup>+</sup> A2F**
**Metr., NPT**


材料	黄铜
密封件	硅橡胶, VMQ
夹紧件	PA 6
防护等级	IP 66, 67 和 68 (5 bar)
环境温度	-60° C – 105° C (-76° F – 221° F)



提示:  
- 铝制和不锈钢材质请垂询



AG	尺寸	$\varnothing$ A1 mm	GL mm	H max. mm	$\varnothing$ mm	D mm	订货号	订货号 黄铜镀镍
M 16 x 1,5	20-1	6-12	16	36,5	22	27	1.608.1600.50	1.608.1603.50
M 20 x 1,5	20-1	6-12	16	36,5	22	27	1.608.2000.50	1.608.2003.50
M 20 x 1,5	20-2	9-16	16	41	24	29	1.608.2000.51	1.608.2003.51
M 25 x 1,5	20-3	12,5-20,5	16	48	30	35	1.608.2500.50	1.608.2503.50
M 32 x 1,5	25	16,9-26	16	48,5	36	42	1.608.3200.50	1.608.3203.50
M 40 x 1,5	32	22-33	16	54	46	52	1.608.4000.50	1.608.4003.50
M 50 x 1,5	40	28-41	16	60	55	64	1.608.5000.50	1.608.5003.50
M 63 x 1,5	50	40-52,6	16	67	65	73	1.608.6300.50	1.608.6303.50
M 75 x 1,5	63	51-65,3	16	72	80	90	1.608.7500.50	1.608.7503.50
NPT 3/8 "	20-1	6-12	16	35,6	22	27	1.608.3800.70	1.608.3803.70
NPT 1/2 "	20-1	6-12	20	35,6	22/24	27	1.608.1200.70	1.608.1203.70
NPT 1/2 "	20-2	9-16	20	39,7	24	29	1.608.1200.71	1.608.1203.71
NPT 3/4 "	20-3	12,5-20,5	20,5	47,5	30	35	1.608.3400.70	1.608.3403.70
NPT 1"	25	16,9-26	25	47,8	36	42	1.608.1000.70	1.608.1003.70
NPT 1 1/4 "	32	22-23	26	51,1	46	52	1.608.5400.70	1.608.5403.70
NPT 1 1/2 "	40	28-41	26,5	56,8	55	64	1.608.6400.70	1.608.6403.70
NPT 2"	50	40-52,6	27	65,4	65	73	1.608.2000.70	1.608.2003.70
NPT 2 1/2 "	63	51-61	40	70,3	80	90	1.608.5200.70	1.608.5203.70
NPT 3"	75	62-78	41,5	76,2	95	107	1.608.3000.70	1.608.3003.70